





2		1					
PART NUMBER	DESCRIPTION	MATERIAL	QTY.				
ESP1281421	esp-df standard fra	ME 6063-T6	1				
ESP1280425	ESP-FLEX STANDARD FR/	AME 6063-T6	2				
ESP1280415	ESP-BLEED TRIM	6063-T6	2				
ESP1280140	7 1/4" X 3" X 3" X 3/16" At	NGLE 6063-T6	4	D			
ESP1280307	1 3/4" X 3" X 3" X 3/16" Gl	JSSET 6063-T6	8				
				1			

1) ESP-DF KIT WITH FLEX STANDARD AND BLEED TRIM CONSISTS OF QTY (4) ESP-DF FRAME PIECES, QTY (4) CORNER ANGLES, QTY (8) FLEX STANDARD FRAME PIECES, QTY (8) FRAME GUSSETS, AND QTY (8) BLEED TRIM PIECES

3) GUSSETS ARE USED TO GUIDE RETAINER PIECES INTO POSITION (IF APPLICABLE)

4) HINGED FRAME SECTION AND HINGED RETAINERS SHOWN TO BE ON TOP OF SIGN CABINET (IF APPLICABLE) 5) SELF DRILLING SCREWS / RIVETS / LOCK CYLINDERS ETC (BY OTHERS) TO SECURE RETAINERS AS NEEDED
6) ANGLES AND GUSSETS TYPICALLY WELDED TO FRAMING (BY OTHERS)
7) 6" - 8" CENTER TO CENTER SPACING RECOMMENDED FOR FLEX CLIPS

9) H1 / H1.5 RETAINERS ALLOW SECONDARY FACE TO BE MOUNTED BEHIND PRIMARY FACE

EXCELLART SIGN PRODUCTS, LLC	UNLESS OTHERWISE SPECIFIED:	ASSEMBLY ID:					
1654 S. LONE ELM RD. OLATHE, KS 66061	DIMENSIONS ARE IN INCHES TOLERANCES	ESPS-DF-FLEXBTDF					
(800) 627-9044 SALES@EXCELLART.COM	FRAC = ±1/32" X.XX = ±0.03 X.XXX = ±0.010	DESCRIPTION:					
WWW.EXCELLART.COM	ANGULAR: MACH±1 BEND ±2	ESP-DI	ESP-DF STANDARD W. FLEX AND BLEE				
		DRAWN BY: EXCELLART		APPROVED BY:			
	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF EXCELLART SIGN PRODUCTS, LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF EXCELLART SIGN PRODUCTS, LLC IS PROHIBITED.	SIZE	Weigh	nt: <b>92.9</b>	2	(lbs)	REV
		C	Perimeter Length: 19 (ft)			-	
CONTRACTOR OF A		SCALE: 1:8 1/8/2024			2024	SHEET 3 OF 3	
			1				

С

В