

4

3

2

1

COVER

D

D

C


C

B

B

A

A



ISO VIEW (EXPLODED)

ISO VIEW

4

3

2

1

EXCELLART SIGN PRODUCTS, LLC. 1654 S. LONE ELM RD. OLATHE, KS 66061 (800) 627-9044 SALES@EXCELLART.COM WWW.EXCELLART.COM		UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES FRAC = ± 1/32" X.XX = ± 0.03 X.XXX = ± 0.010 ANGULAR: MACH ± 1 BEND ± 2		ASSEMBLY ID: ESPS-6-FLEXBTDF	
		PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF EXCELLART SIGN PRODUCTS, LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF EXCELLART SIGN PRODUCTS, LLC IS PROHIBITED.		DESCRIPTION: ESP-6 W. FLEX AND BLEED TRIM	
		DRAWN BY: EXCELLART		APPROVED BY:	
		SIZE C	Weight: 81.30 (lbs)	REV -	SCALE: 1:8 1/8/2024 SHEET 1 OF 3





4

3

2

1

DIMS



SECTION A-A
ESP-6 FRAME W/ ESP-FLEX STANDARD
FRAMES AND BLEED TRIM
SCALE 1 : 1

SECTION B-B
ESP-6 FRAME W/ ESP-FLEX STANDARD
FRAMES AND BLEED TRIM
SCALE 1 : 1

EXCELLART SIGN PRODUCTS, LLC. 1654 S. LONE ELM RD. OLATHE, KS 66061 (800) 627-9044 SALES@EXCELLART.COM WWW.EXCELLART.COM		UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES		ASSEMBLY ID: ESPS-6-FLEXBTDF	
		TOLERANCES: FRAC = ± 1/32" X.XX = ± 0.03 X.XXX = ± 0.010 ANGULAR: MACH ± 1 BEND ± 2		DESCRIPTION: ESP-6 W. FLEX AND BLEED TRIM	
EXCELLART <small>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF EXCELLART SIGN PRODUCTS, LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF EXCELLART SIGN PRODUCTS, LLC IS PROHIBITED.</small>		PROPRIETARY AND CONFIDENTIAL DRAWN BY: EXCELLART		APPROVED BY:	
		SIZE C	Weight: 81.30 (lbs)	REV	PERIMETER LENGTH: 19 (ft)
SCALE: 1:8		1/8/2024		SHEET 2 OF 3	

4

3

2

1

D

D

C

C

B

B

A

A

4

3

2


1

BOM

ITEM NO.	PART NUMBER	DESCRIPTION	MATERIAL	QTY.
1	ESP1280126	ESP-6 FRAME	6063-T6	1
2	ESP1280425	ESP-FLEX STANDARD FRAME	6063-T6	2
3	ESP1280415	ESP-BLEED TRIM	6063-T6	2
4	ESP1280123	3 11/16" X 3" X 3" X 3/16" ANGLE	6063-T6	4
5	ESP1280307	1 3/4" X 3" X 3" X 3/16" GUSSET	6063-T6	8

NOTES:

- 1) ESP-6 KIT WITH FLEX STANDARD AND BLEED TRIM CONSISTS OF QTY (4) ESP-6 FRAME PIECES, QTY (4) CORNER ANGLES, QTY (8) ESP-FLEX STANDARD FRAME PIECES, QTY (8) FRAME GUSSETS, AND QTY (8) BLEED TRIM PIECES
- 2) ANGLES ARE USED TO GUIDE FRAME PIECES INTO POSITION
- 3) GUSSETS ARE USED TO GUIDE RETAINER PIECES INTO POSITION (IF APPLICABLE)
- 4) HINGED FRAME SECTION AND HINGED RETAINERS SHOWN TO BE ON TOP OF SIGN CABINET (IF APPLICABLE)
- 5) SELF DRILLING SCREWS / RIVETS / LOCK CYLINDERS ETC (BY OTHERS) TO SECURE RETAINERS AS NEEDED
- 6) ANGLES AND GUSSETS TYPICALLY WELDED TO FRAMING (BY OTHERS)
- 7) 6" - 8" CENTER TO CENTER SPACING RECOMMENDED FOR FLEX CLIPS
- 8) PIANO HINGES USED TO ALLOW IDS RETAINERS TO HINGE OPEN (IF APPLICABLE)
- 9) H1 / H1.5 RETAINERS ALLOW SECONDARY FACE TO BE MOUNTED BEHIND PRIMARY FACE
- 10) EXCELLART UL FILE NUMBER: E152309



ISO VIEW (EXPLODED)

EXCELLART SIGN PRODUCTS, LLC.
 1654 S. LONE ELM RD.
 OLATHE, KS 66061
 (800) 627-9044
 SALES@EXCELLART.COM
 WWW.EXCELLART.COM



UNLESS OTHERWISE SPECIFIED:
 DIMENSIONS ARE IN INCHES
 TOLERANCES:
 FRAC = ± 1/32"
 X.XX = ± 0.03
 X.XXX = ± 0.010
 ANGULAR: MACH ± 1 BEND ± 2

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF EXCELLART SIGN PRODUCTS, LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF EXCELLART SIGN PRODUCTS, LLC IS PROHIBITED.

ASSEMBLY ID: ESPS-6-FLEXBTDF	
DESCRIPTION: ESP-6 W. FLEX AND BLEED TRIM	
DRAWN BY: EXCELLART	APPROVED BY:
SIZE C	Weight: 81.30 (lbs) REV
	Perimeter Length: 19 (ft) -
SCALE: 1:8	1/8/2024 SHEET 3 OF 3

4

3

2

1

D

D

C

C

B

B

A

A